

Description	PI380/3	PI220/3	PI380/4	PI220/4
Motor				
Voltage	380V triphased	220V triphased	380V triphased	220V triphased
Power	3KW (4CV)	3KW (4CV)	4KW (5.5CV)	4KW (5.5CV)
Amperage				
Speed	2850 rev/min,	2850 rev/min	2850 rev/min	2850 rev/min
Millstones				
Diameter	20 cm			
Composition	amalgam of corundum/Naxos, bound with natural manesia cement, cast in aluminium support			
Funnel	Stainless steel, capacity of 35 kg (Wheat)			
Yield				
Finest grind	60 à 80 kg/hour		80 à 100 kg/hour	
Fine grinde (bread)	80 à 100 kg/hour		100 à 120 kg/hour	
Coarse crushing	100 à 120 kg/hour		120 à 150 kg/hour	
Noise				
L wa (dB)	82			
Equiment	Thermical overload protection Ammeter Time counter		Thermical overload protection Ammeter Time counter Timer	
Dimensions				
Height	1.35m		1.35m	
Length	0.85m		0.85m	
Width	0.60m		0.60m	
Gross weight	95 kg		100 kg	
Possible options	Casters Stabilization pads		Casters Stabilization pads Specialized chestnut millstone	